



Dock Master LED Loading Dock Light

- Operating temperature of -20°F to 120°F
- Voltage Input – 100 to 240 AC, 50/60 HZ, Single Phase
- Rated for "wet locations" and IP66
- Built with an extruded aluminum outer skin making it completely shock resistant
- Polycarbonate plastic lens is built to sustain high impact without cracking or scratching
- Comes in a cool white colour with high CRI value to show true colour rendering
- Intertec ETL certified, conforms under UL, ULc, CE and CSA
- Ideal for use in food and pharmaceutical facilities
- Available as a complete Loading Dock fixture with arm or just the LED head unit



80% ENERGY SAVINGS

Truly the Last LED Loading Dock Light You'll Ever Have to Buy!

Serviceable

The Dock Master LED Dock Light uses the newest Array system technology that combines "Smart Thermal Management" with high consistent lumen output. In addition, unlike other dock lights, the Dock Master's LED array is a serviceable component of the entire unit, which allows the owner, after the 65,000 hours or 5 year warranty, to replace the emitter only within the fixture and continue using the fixture for years to come.

Long Lasting

Within the Dock Master LED Dock Light's head is an LED power driver which has been rated for 300,000 hours of use - in other words, at 12 hours per day of usage, the Dock Master LED Loading Dock Light could last a total of 69 years!

**BACKED BY A
5-YEAR WARRANTY**

Liftway
MATERIAL HANDLING SOLUTIONS