

# MOBILE TELESCOPIC HYDRAULIC STACKERS

**MODELS: FTAFC96  
FTAFC120  
FTAFC132  
FTAFC144**

When a high lift capability is required but aisle space is limited then the Mobile Telescopic Hydraulic Stackers are the answer.

Combining power lift with easy to maneuver manual push, the FTAFC Series stackers are designed to lift Skids, Bales, Baskets, etc.; are perfect for racking and shelving applications as well as loading and unloading trucks where there are no docks; and can handle Pallets of all sizes due to their Adjustable Straddle Legs.

Providing a safe ergonomic alternative to fork lift trucks at a fraction of the cost, the FTAFC Stackers are easy to use, are designed to handle constant heavy duty use, need no special training to operate, and require a minimum of maintenance.



## FEATURES:

**Frame:** Rugged heavy duty frame constructed of formed and welded steel for extra strength.

**Mast:** Fabricated with channel steel for greater strength and dependability. Open structure design complete with safety cage offers greater visibility.

**Lifting Chains:** Unique dual lifting chains are roller style, heavy duty steel exceeding a 6:1 safety factor.

**Hydraulic System:** Durable cylinder features a chrome plated ram and a relief valve for overload protection.

**Forks:** Heavy duty steel 1.5" deep X 3" wide X 42" long adjustable forks.

**Adjustable Straddle Legs:** The straddle legs offer complete versatility by adjusting from 36" to 50" I.D.

**Battery:** Features a heavy duty 12 volt, 125 amps/hour industrial strength battery.

**Charger:** The built-in battery charger is a 10 amp Selenium rectifier with transformer, circuit breaker and overload protection, and plugs into any 110 volt outlet.

**Steering:** Mounted in the center of the lower housing, the 5<sup>th</sup> wheel improves steering in tight areas and features 7" X 2" phenolic wheels.

**Wheels:** Standard front wheels are phenolic and are available in 4" or 7" diameter sizes with roller bearings.

**Brake:** Features a hand controlled floor lock brake that secures the unit in place.

**Options:**  
2,000 lb. capacity (96" model only)  
Fixed Straddle Legs to 50" I.D.  
AC Power  
Remote Control  
Snap-on Platform  
Modified Fork Length  
Work Platform w/safety rail

## SPECIFICATIONS:

Load Capacity:	1500 lbs.
Load Center:	24"
Lowered Fork Height:	3"
Raised Height:	96/120/132/144"
Mast Height:	70/82/88/94"
Straddle Legs I.D.:	36" - 50"
Straddle Legs O.D.:	42" - 56"
Fork Size:	1.5" X 3" X 42"
Fork Adjust O.D.:	6" - 25"
Weight:	815/875/900/924 lbs.
Steer Wheels:	7" Phenolic
Front Wheels:	4" Phenolic
Battery:	12V/125A heavy duty
Charger:	12V/10A w/overload protect