



Exceptional access to engine and related components makes machine maintenance easy.

# 9000 Series

## Double Scrubbers

*Efficiently and Effectively  
Scrub Floors Twice  
in One Pass.*



**Two Models (9082 and 9090)  
Pre-Sweep and Aggressively  
Scrub Any Worksite!**



Disk scrub brushes, sweeping brooms and squeegees can be easily removed in minutes - without tools!

**Minuteman<sup>®</sup>**  
**PowerBoss<sup>®</sup>**

# 9000 Series Features

- Sweep paths range from 42" (9082) to 60" (9090).
- Scrub paths range from 42" to 56" path with optional side scrub brush.
- All steel construction.
- Up to 100-gal. (120L) molded polyethylene tanks extend scrub time.
- Tanks are rust-free and easy-to-fill and easy-to-drain.
- Cleans up to 91,500 sq. ft. per hour with optional side scrub brush.
- Compact size for excellent maneuverability when working in congested or high-traffic areas.
- Premium quality components throughout mean less service and replacement.
- Excellent engine and related components accessibility when the engine cover is raised.
- Direct-throw sweeper provides clean, reliable debris pickup—and pre-sweep feature removes light litter before applying water for scrubbing.
- Large screw-on cap provides easy access to rugged, high-density polyethylene tanks. These tanks won't rust or leak—and come with a five-year warranty.
- Automatic lift-in-reverse mechanism protects squeegee assembly when backing up.
- Easy access doors open for fast, no-tool broom, brush and squeegee changes.
- Disk scrub brushes, sweeping brooms and squeegees can be easily removed in minutes.

## MODEL 9082 DOUBLE SCRUBBER w/both Disc and Cylindrical Scrub Brushes up to 50" scrubbing path\*

### GENERAL SPECIFICATIONS

**POWER:** Transverse, mid-engine design. 53 HP (39.6 kw), 4-cylinder, liquid-cooled gasoline engine. Electric start, 12-volt battery. Eight gallon (30.3L) gas tank. Optional: LP gas or 37.5 HP (27.9 kw), 4-cylinder, liquid-cooled diesel engine. 4-core radiator standard on all models.

**FRAME:** Unitized construction featuring 3/16-inch (4.8mm) steel plate, reinforced at stress points.

**DRIVES:** Hydraulically-driven rear wheel. Variable speeds to 8 mph (12.87 kmh). Main and side brooms, scrub brushes and vacuum impeller are hydraulically operated.

**STEERING:** Standard power steering through rear tire.

**SWEEPING COVERAGE:** 67,000 sq. ft. (6,224m<sup>2</sup>) per hour based on 42-inch (1,067mm) path at 4 mph (6.44kmh) with 4-inch (102mm) overlap or 77,500 sq. ft. (7,200m<sup>2</sup>) per hour with optional side brush.

**DEBRIS HOPPER:** 5 cu. ft. (0.14m<sup>3</sup>); aluminum construction. Manual lift-out dumping.

**SCRUB PATH:** 42-inch (1,067mm) scrub path or 50-inch (1,270mm) path with optional side scrub brush.

**SCRUBBING BRUSHES:** Three rotary 14-inch (356mm) OD quick-change brushes are hydraulically driven. (Side scrub brush optional.) And one 42" cylindrical scrub.

**SCRUBBING COVERAGE:** 67,000 sq. ft. (6,224m<sup>2</sup>) per hour based on 42-inch (1,067mm) path at 4 mph (6.44kmh) with 4-inch (102mm) overlap or 77,500 sq. ft. (7,200m<sup>2</sup>) per hour with optional side brush.

**SOLUTION TANK:** 68-gallon (257L) capacity with automatic water shutoff. Non-rusting high-density polyethylene five-year warranty. Optional stainless steel.

**RECOVERY TANK:** 65-gallon (246L) capacity. Non-rusting high-density polyethylene five-year warranty. Flexible drain hose and oversized cleanout ports provide easy emptying and cleaning. Optional stainless steel.

**VACUUM PICK-UP:** High-speed 9-inch (229mm) impeller provides water pick-up through rear squeegee.

**SQUEEGEES:** Rear: one 44-inch (1,118mm) parabolic squeegee. Quick-change rubber. Side: Two floating side squeegees on sides of scrub head.

**SQUEEGEE ASSEMBLY:** Rear and side squeegees remove from machine in minutes. No tools required.

**CONTROLS:** Operator controls all functions of sweeping and scrubbing while seated. Instant forward, reverse and braking using one pedal. Foot pedal activates emergency/parking brake.

**INSTRUMENTS:** Ammeter, hour meter, electric fuel gauge, oil pressure, water temperature.

**TIRES:** Front: Two 16-inch (406mm) OD industrial solid. Rear: One 16-inch (406mm) OD industrial solid. Tire options available.

**WEIGHT:** Net: 2,700 lbs. (1,224kg)  
Shipping: 3,100 lbs. (1,406kg)  
Both approximate.

**DIMENSIONS:** Length: 91 inches (2,311 mm); Width: 48 inches (1,291 mm); Height: 57 inches (1,448 mm)  
•with overhead guard: 87 inches (2,210 mm) •with cab: 83-1/2 inches (2,121 mm)

**OPTIONS:** Ask your representative about a wide range of options.

\*with optional side brush

*Subject to change without notice.*

## MODEL 9090 DOUBLE SCRUBBER w/both Disc and Cylindrical Scrub Brushes up to 56" scrubbing path\*

### GENERAL SPECIFICATIONS

**POWER:** Transverse, mid-engine design. 53 HP (39.6 kw), 4-cylinder, liquid-cooled gasoline engine. Electric start, 12-volt battery. Eight gallon (30.3L) gas tank. Optional: LP gas or 46 HP (27.9 kw), 4-cylinder, liquid-cooled diesel engine. 4-core radiator standard on all models.

**FRAME:** Unitized construction featuring 3/16-inch (4.8mm) steel plate, reinforced at stress points.

**DRIVES:** Hydraulically-driven rear wheel. Variable speeds to 10 mph (16.09 kmh). Main and side brooms, scrub brushes and vacuum impeller are hydraulically operated.

**STEERING:** Standard power steering through rear tire.

**SWEEPING COVERAGE:** 77,500 sq. ft. (7,200m<sup>2</sup>) per hour based on 48-inch (1,219mm) path at 4 mph (6.44kmh) with 4-inch (102mm) overlap or 91,000 sq. ft. (8,500m<sup>2</sup>) per hour with optional side brush.

**DEBRIS HOPPER:** 6 cu. ft. (0.17m<sup>3</sup>); aluminum construction. Manual lift-out dumping.

**SCRUB PATH:** 48-inch (1,219mm) scrub path or 56-inch (1,422mm) path with optional side scrub brush.

**SCRUBBING BRUSHES:** Three rotary 16-inch (406mm) OD quick-change brushes are hydraulically driven. (Side scrub brush optional.) And one 48" cylindrical scrub.

**SCRUBBING COVERAGE:** 77,500 sq. ft. (7,200m<sup>2</sup>) per hour based on 48-inch (1,219mm) path at 4 mph (6.44kmh) with 4-inch (102mm) overlap or 91,000 sq. ft. (8,500m<sup>2</sup>) per hour with optional side brush.

**SOLUTION TANK:** 100-gallon (378.5L) capacity with automatic water shutoff. Non-rusting high-density polyethylene five-year warranty. Optional stainless steel.

**RECOVERY TANK:** 100-gallon (378.5L) capacity. Non-rusting high-density polyethylene five-year warranty. Flexible drain hose and oversized cleanout ports provide easy emptying and cleaning. Optional stainless steel.

**VACUUM PICK-UP:** High-speed 9-inch (229mm) impeller provides water pick-up through rear squeegee.

**SQUEEGEES:** Rear: one 50-inch (1,270mm) parabolic squeegee. Quick-change rubber. Automatically raised when unit backs up. Side: Two floating side squeegees on sides of scrub head.

**SQUEEGEE ASSEMBLY:** Rear and side squeegees remove from machine in minutes. No tools required.

**CONTROLS:** Operator controls all functions of sweeping and scrubbing while seated. Instant forward, reverse and braking using one pedal. Foot pedal activates emergency/parking brake.

**INSTRUMENTS:** Ammeter, hour meter, electric fuel gauge, oil pressure, water temperature.

**TIRES:** Front: Two 16-inch (406mm) OD industrial solid. Rear: One 16-inch (406mm) OD industrial solid. Tire options available.

**WEIGHT:** Net: 3,000 lbs. (1,361 kg)  
Shipping: 3,400 lbs. (1,542kg)  
Both approximate.

**DIMENSIONS:** Length: 95 inches (2,413 mm); Width: 54 inches (1,372 mm); Height: 58 inches (1,473 mm)  
•with overhead guard: 87 inches (2,210 mm) •with cab: 83-1/2 inches (2,121 mm)

**OPTIONS:** Ask your representative about a wide range of options.

\*with optional side brush

*Subject to change without notice.*

**Minuteman<sup>®</sup>**  
**PowerBoss<sup>®</sup>**

World Headquarters

Minuteman International, Inc.

111 South Rohlwing Road • Addison, IL 60101-4244

Telephone: (630) 627-6900 • Fax: (630) 627-1130

www.minutemanintl.com

Minuteman PowerBoss

175 Anderson Street • Aberdeen, NC 28315

Telephone: (910) 944-2105 • Fax: (910) 944-7409

www.powerboss.com

Minuteman is a full line manufacturer of maintenance products including critical filter vacuums, industrial and commercial vacuums, sweepers, scrubbers, floor and carpet machines, PowerBoss<sup>®</sup> sweepers and scrubbers, Parker Sweeper<sup>®</sup> Litter Vacs and Multi-Clean<sup>®</sup> chemicals for industrial, commercial, and institutional facilities.

