

SOLIDEAL ECOMATIC TRACTION



IMPERIAL UNIT

PRESS-ON
TIRES



PERFORMANCE WHEN YOU NEED IT.

Best-in-class and ideal for low-intensity material handling applications. With its natural rubber compounds it delivers maximum life where premium technology is not required.

camsso.co

PERFORMANCE

Durability



Energy Savings



Tire Life



**ROAD
FREE
COMPANY**

FORMERLY
CAMOPLAST
SOLIDEAL

SOLIDEAL ECOMATIC TRACTION

TIRE SIZE ⁽¹⁾	ACTUAL TIRE DIMENSIONS			LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (lbs)					
	OVERALL DIAMETER (in)	OVERALL WIDTH (in)	REPLACEMENT OVERALL DIAMETER ⁽³⁾ (in)	6 mph		10 mph		16 mph	
				LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
14 x 4 1/2 x 8	13.9	4.5	12.1	2568	2105	2293	1929	1863	1532
16 x 5 x 10 1/2	15.9	5.0	14.3	3318	2734	2965	2491	2414	1973
16 x 6 x 10 1/2	15.9	6.0	14.3	4200	3450	3748	3153	3053	2502
16 1/4 x 5 x 11 1/4	16.1	5.0	14.7	3362	2756	2998	2524	2436	1995
16 1/4 x 6 x 11 1/4	16.1	6.0	14.7	4222	3461	3770	3164	3064	2513
18 x 6 x 12 1/8	17.9	6.0	16.1	4608	3781	4112	3450	3340	2745
18 x 7 x 12 1/8	17.9	7.0	16.1	5633	4630	5026	4222	4090	3351
18 x 8 x 12 1/8	17.9	8.0	16.1	6614	5434	5908	4960	4806	3935
21 x 7 x 15	20.9	7.0	19.1	6327	5203	5655	4751	4597	3770
21 x 8 x 15	20.9	8.0	19.1	7441	6118	6647	5578	5401	4431
22 x 9 x 16	21.8	9.0	20.1	8918	7330	7970	6691	6482	4718



NATURAL RUBBER COMPOUND

- Provides good overall wear and performance

HUGE LUG DEPTH

- Increases life and traction

Non-marking compound availability on request



AUTHORIZED DISTRIBUTOR:

Remarks

- (1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0.005"/-0" • Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3 μm • Chamfer 5 mm wide @ 30°
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.
- (3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter. All specifications for non-marking tires are the same as the equivalent standard black tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camso.co



FORMERLY
CAMOPLAST
SOLIDEAL

SOLIDEAL ECOMATIC TRACTION



METRIC UNIT

PRESS-ON
TIRES



PERFORMANCE WHEN YOU NEED IT.

Best-in-class and ideal for low-intensity material handling applications. With its natural rubber compounds it delivers maximum life where premium technology is not required.

camsso.co

PERFORMANCE

Durability



Energy Savings



Tire Life



FORMERLY
CAMOPLAST
SOLIDEAL

SOLIDEAL ECOMATIC TRACTION

TIRE SIZE ⁽¹⁾	ACTUAL TIRE DIMENSIONS			LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (kg)					
	OVERALL DIAMETER (mm)	OVERALL WIDTH (mm)	REPLACEMENT OVERALL DIAMETER ⁽³⁾ (mm)	10 kmh		16 kmh		25 kmh	
				LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
14 x 4 1/2 x 8	354	114	308	1165	955	1040	875	845	695
16 x 5 x 10 1/2	404	127	363	1505	1240	1345	1130	1095	895
16 x 6 x 10 1/2	403	152	362	1905	1565	1700	1430	1385	1135
16 1/4 x 5 x 11 1/4	410	127	373	1525	1250	1360	1145	1105	905
16 1/4 x 6 x 11 1/4	410	152	373	1915	1570	1710	1435	1390	1140
18 x 6 x 12 1/8	454	152	410	2090	1715	1865	1565	1515	1245
18 x 7 x 12 1/8	454	178	410	2555	2100	2280	1915	1855	1520
18 x 8 x 12 1/8	454	203	410	3000	2465	2680	2250	2180	1785
21 x 7 x 15	531	178	485	2870	2360	2565	2155	2085	1710
21 x 8 x 15	530	203	485	3375	2775	3015	2530	2450	2010
22 x 9 x 16	554	229	510	4045	3325	3615	3035	2940	2140



NATURAL RUBBER COMPOUND

- Provides good overall wear and performance

HUGE LUG DEPTH

- Increases life and traction

Non-marking compound availability on request



AUTHORIZED DISTRIBUTOR:



Brantford, ON. N3T 5N9
1-800-543-8929
sales@liftway.on.ca

Remarks

- (1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0.005"/-0" • Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3 µm • Chamfer 5 mm wide @ 30°
- (2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.
- (3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter. All specifications for non-marking tires are the same as the equivalent standard black tire.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.



Camso is the best of Camoplast and Solideal.
To keep moving forward while staying true to our history,
we're now the Road Free company.

camsso.co



FORMERLY
CAMOPLAST
SOLIDEAL